

Section 1 – Identification of the Substance/Preparation and of the Company/Undertaking

| | | | |
|-----------------------|----------------------------------|------------------------------------|---|
| Product Name: | POLISH REMOVER | MSDS# | KIA103002- |
| Chemical Name: | N/A | : | NPR |
| Family: | SOLVENTS | MSDS Initial Approval Date: | 10/30/2002 |
| Product Use: | ACRYLIC NAIL REMOVER APPLICATION | MSDS Prepared by: | BSQ |
| Product #: | 4020040 | Manufacturer: | Shanghai Kaicheng Technology Comany |
| | | | 5G, Building 4, NO.398, South Henan Road, Shanghai, China, 200010 |
| | | Emergency Phone Numbers: | (86-21) -63340465 |
| | | Information Contacts: | (86-21) -33023293 |

Section 2 - Composition/Information on Ingredients

| Chemical Identity | CAS Numbers | EINECS# | INCI Name | Exposure OSHA TWA/STEL | Limits ACGIH TWA/STEL | Carcinogen IARC/NTP/OSHA | % |
|---------------------|-------------|-----------|---|------------------------|-----------------------|--------------------------|-------|
| Methyl Ethyl Ketone | 78-93-3 | 201-159-0 | MEK | 200 ppm | 200 ppm | no/no/no | 60-70 |
| Isopropyl Alcohol | 67-63-0 | 200-661-7 | Isopropyl Alcohol | 400 ppm | 400 ppm | 3/no/no | 30-40 |
| Lavender Fragrance | 84776-65-8 | 283-994-0 | Lavandula Angustifolia (Lavender) Extract | N/DA | N/DA | Not Listed | 0-1 |

N/E - None Established N/DA - No Data Available
 N/R - Not Reviewed N/A - Not Applicable

Hazard Symbols: Xn, F **Risk Phrases:** R11, R20/22, R36/37/38 **Safety Phrases:** S7/9, S16, S24/25, S33, S37/39, S45

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.

- **Flammable liquid and vapor!**
- May cause allergic skin reaction.
- May cause eye irritation.
- May cause respiratory tract irritation.



Potential Health Effects, Signs and Symptoms of Exposure:

| | |
|------------------------|--|
| Primary Route of Entry | Inhalation, skin contact, eye contact |
| Eye | Exposure causes eye irritation. Symptoms include stinging, tearing, redness and swelling. |
| Skin | Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking, and skin burns. |
| Ingestion | Swallowing small amounts during normal handling is not likely to cause harmful effects; swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. |
| Inhalation | Vapor and mist are irritating to mucous membrane. Breathing small amounts during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits. |
| Sub-Chronic Effects | It may cause headaches, nausea, vomiting and narcotic effect if over-exposed. |

NOTE: Refer to Section 11, Toxicological Information for Details

Section 4 - First Aid Measures

| | |
|--------------------------|---|
| First Aid for Eye | If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention. |
| First Aid for Skin | Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. |
| First Aid for Inhalation | Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persist, seek medical attention. |
| First Aid for Ingestion | If individual is drowsy or unconscious. do not give anything by mouth; place individual on the left side with the head down. Seek medical attention for advice about whether to induce vomiting. If possible, do not leave individual unattended. |

Section 5 - Fire Fighting Measures

| | | |
|--------------------|------------------------|----------------------------------|
| Flash Point | Flammable Limit | Auto-ignition Temperature |
|--------------------|------------------------|----------------------------------|



Material Safety Data Sheet

NON-ACETONE POLISH REMOVER

| | | |
|-----------------------|---------|--------|
| (°F/°C) | (vol%) | (vol%) |
| TAG Closed: 68°F/20°C | 400 ppm | N/DA |

| | |
|----------------------|---|
| Method: | |
| Extinguishing Media: | Foam, dry chemical, cold water spray. |
| Fire Fighting | Wear self-contained breathing apparatus and protective clothing. USE WATER WITH CAUTION. Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a safe distance and protected location. |
| Instructions: | |
| Unusual Hazards: | Flammable. When exposed to heat and flame, material is a fire explosion hazard. It may produce toxic products CO, Carbon dioxide and oxides of nitrogen. Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations. |

Section 6 - Accidental Release Measures

Spill or Release Procedures
Eliminate all sources of heat and ignition. Use absorbent material for spills and dike it, wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as sawdust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

Section 7 - Handling and Storage

Handling
Keep containers cool and dry. Keep away from heat, light and ignition sources. Avoid breathing high vapor concentrations. Avoid prolonged or repeated contact with skin. Use only with adequate ventilation. Wash thoroughly after handling.

Storage
Store in well ventilated area. Store @ 70°F+/- 15°F (21°C+/-8°C), allow some air space above liquid level. Keep containers closed while not in use.

Explosion Hazard
Vapors are heavier than air and may travel along the ground or may be move by ventilation and ignited by pilot lights, other flames,sparks,heaters,smoking or other ignition sources at locations distant from material handling point.Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Section 8 - Exposure Controls / Personal Protective Equipment

Engineering Controls
Facilities storing or utilizing this material should be equipped with an eye facility and safety shower. Use process enclosures local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.

Personal Protective Equipment

General
To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product . Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.

Eye/ Face Protection
Use impermeable clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.

Skin Protection
Wear resistant gloves.To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protection
A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

Section 9 - Physical and Chemical Properties

| Appearance | Odor & Odor Threshold | pH | Specific Gravity | Viscosity | % Volatile |
|-----------------------------|-----------------------|----|------------------|-----------|------------|
| Clear/Purple,viscous liquid | fruity ester odor | NA | (H2O=1):0.98 | N/DA | W/W %: 99+ |

| Boiling Point/ | Decomposition | Octanol/Water | Vapor | Vapor | Evaporation | Ignition | Solubility |
|----------------|---------------|---------------|-------|-------|-------------|----------|------------|
| | | | | | | | |



Material Safety Data Sheet

NON-ACETONE POLISH REMOVER

| Freezing Point | Temperature | Partitioning Coefficient Log Po/w | Pressure | Density | Rate | In Water (20°C) |
|----------------|-------------|--------------------------------------|----------|-----------|------|-----------------|
| 170°F/77°C | N/DA | N/DA | N/DA | (Air=1):1 | N/DA | Insoluble |

| Flash Point (°F/°C) | Flammable Limit (vol%) | Auto-ignition Temperature (vol%) |
|-----------------------|------------------------|----------------------------------|
| TAG Closed: 68°F/20°C | 400 ppm | N/DA |

Section 10 - Stability and Reactivity

| | |
|--|--|
| Stability: Stable | Incompatibility (Materials to Avoid): Avoid oxidizing agents, acids & bases (heat) |
| Hazardous Decomposition Products: Heated material produce NO ₂ , CO ₂ , CO | Hazardous Polymerization: Will not occur |
| Conditions to Avoid: Heat, flame, ignition sources. | |

Section 11 - Toxicological Information

| Acute Oral Toxicity | Acute Dermal Toxicity | Acute Inhalation Toxicity | Irritation - skin | Irritation - Eye |
|---|--------------------------|---------------------------|--------------------------|------------------|
| No information available | No information available | No information available | No information available | N/DA |
| Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals. | | | | |
| Sensitization | Mutagenicity | Sub-chronic Toxicity | | |
| No information available | No information available | No information available | | |

Section 12 - Ecological Information

Ecotoxicological Information

| Acute Toxicity To Fish | Acute Toxicity to Invertebrates | Acute Toxicity to Algae | Bioconcentration | Toxicity to Sewage Bacteria |
|--------------------------|---------------------------------|-------------------------|------------------|-----------------------------|
| No information available | No information available | N/DA | N/DA | No information available |

Chemical Fate Information

| | |
|-------------------------------|--------------------------|
| Biodegradability | No information available |
| Chemical Oxygen Demand | No information available |

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil.

Section 13 - Disposable Considerations

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements. For EU Member States, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

Section 14 - Transport Information

| | |
|--|--|
| DOT (49 CFR 172) | |
| Proper Shipping Name: | Flammable liquids, n.o.s., (methyl ethyl ketone, isopropyl alcohol), 3, UN1993, PGII |
| Identification Number: | UN1993 |
| Marine Pollutant: | No |
| Special Provisions: | T8, T31 |
| Emergency Response Guidebook (ERG) #: | 128 |
| IATA (DGR): | |
| Proper Shipping Name: | Flammable liquids, n.o.s., (methyl ethyl ketone, isopropyl alcohol), 3, UN1993, PGII |
| Class or Division: | 3 |
| UN or ID Number: | UN1993 |
| Packaging Instructions: | |
| Emergency Response Guidance (ICAO)#: | 3L |
| IMO (IMDG): | |
| Proper Shipping Name: | Flammable liquids, n.o.s., (methyl ethyl ketone, isopropyl alcohol), 3, UN1993, PGII |

Material Safety Data Sheet

NON-ACETONE POLISH REMOVER

Page 4 of 5

| | |
|---|--------------------|
| Class or Division: | 3.2 |
| UN or ID Number: | UN1993 |
| Special Provisions & Stowage/Segregation: | None |
| Emergency Schedule (EmS)#: | 307 |
| Other Information: | Flash point = 20°C |

Section 15 - Regulatory Information

US Federal Regulations

| | |
|---|---|
| Clean Air Act: HAP/ODS | This product contains the following hazardous air pollutants (HAPs): <ul style="list-style-type: none"> Methyl Ethyl Ketone, CAS# 78-93-3 There are no ODS's (ozone depleting substances) as defined by the U. S. Clean Air Act. |
| Clean Water Act: Priority Pollutant | This product contains the following chemicals listed under the U. S. Clean Water Act Priority Pollutant and Hazardous Substance List: <ul style="list-style-type: none"> NONE |
| FDA: Food Packaging Status | This product has not been cleared by the FDA for use in food packaging and / or other applications as an indirect food additive. |
| Occupational Safety and Health Act | This product is considered to be hazardous under the OSHA Hazard Communication Standard. Its hazard are: <ul style="list-style-type: none"> Immediate (acute) health hazard Fire hazard |
| RCRA | This product contains chemicals considered to be hazardous waste under RCRA (40 CFR 261): <ul style="list-style-type: none"> Methyl Ethyl Ketone, CAS# 78-93-3, RCRA Codes D035, U159 May contain Characteristic of Ignitability: RCRA Code: D001 |
| SARA Title III: Section 302 (TPQ) | This product contains no chemicals regulated under Section 302 as extremely hazardous substances that carry a TPQ. |
| SARA Title III: Section 302 (RQ) | This product contains chemicals regulated under Section 304 as extremely hazardous chemicals for emergency release notification ("CERCLA" List): <ul style="list-style-type: none"> Methyl Ethyl Ketone CAS#: 78-93-3, RQ(Lbs)5000 |
| SARA Title III: Section 311-312: | This product is considered to be hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are: <ul style="list-style-type: none"> Immediate (acute) health hazard Fire hazard |
| SARA Title III: Section 313: | This product contains the following chemicals which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: <ul style="list-style-type: none"> Isopropyl Alcohol CAS#: 67-63-0 Methyl Ethyl Ketone CAS#: 78-93-3 |
| TSCA Section 8(b): Inventory: TSCA Significant New Use Rule: | This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements. None of the chemicals in this material have a SNUR under TSCA. |

State Regulations

| | |
|--|---|
| CA Right-to-Know Law: California No Significant Risk Level: | Isopropyl Alcohol CAS #67-63-0, Methyl Ethyl Ketone CAS 78-93-3 NONE |
| MA Right-to-Know Law: | Isopropyl Alcohol CAS #67-63-0, Methyl Ethyl Ketone CAS 78-93-3 |
| NJ Right-to-Know Law: | Isopropyl Alcohol CAS #67-63-0, Methyl Ethyl Ketone CAS 78-93-3 |
| PA Right-to-Know Law: | Isopropyl Alcohol CAS #67-63-0, Methyl Ethyl Ketone CAS 78-93-3 |
| FL Right-to-Know Law: | Isopropyl Alcohol CAS #67-63-0, Methyl Ethyl Ketone CAS 78-93-3 |
| MN Right-to-Know Law: | Isopropyl Alcohol CAS #67-63-0, Methyl Ethyl Ketone CAS 78-93-3 |

International Regulations



| | |
|---|--|
| CDSL: Canadian Inventory (on Canadian Transitional List) | Isopropyl Alcohol CAS #67-63-0 is on the DSL list. WHMIS = B2, D2B Methyl Ethyl Ketone CAS 78-93-3 is on the DSL list. WHMIS = B2, D2A Lavandula Angustifolia (Lavender) Extract CAS# 84776-65-8 is on the DSL list. WHMIS = n/da |
| EINECS: European Inventory: | Non-Acetone Polish Remover: <ul style="list-style-type: none"> HAZARD SYMBOLS: Xn, F: Harmful, Highly Flammable RISK PHRASES: R11, highly flammable, R20/22: Harmful by inhalation and if swallowed, R36/37/38: Irritating to eyes, respiratory system and skin |



- SAFETY PHRASES: **S7/9:** keep container tightly closed and in a well ventilated place, **S16:** keep away from sources of ignition- no smoking, **S24/25:** avoid contact with skin and eyes, **S33:** take precautionary measures against static discharges, **S37/39:** wear suitable gloves and eye/face protection, **S45:** In case of accident or if you feel unwell, seek medical advise immediately (show the label where possible)

Section 16 - Other Information

Hazard Rating System (Pictograms)

| | |
|---|---|
| <p>NFPA:</p>  <p>Health →</p> <p>← Flammability</p> <p>← Reactivity</p> | <p>HMIS:</p>  |
|---|---|

Product Number - 4020040

Revised Sections since Last Version: Updating formatting and INCI names.

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800) 535-5053.